




# Welding machine

## IGBT INVERTER GAS/GASLESS MIG/MMA/TIG WELDER



### Standard accessories



Parameter	Model	Multi-GMAW 180	Multi-GMAW 200	Multi-GMAW 250 LCD PFC
Input Voltage (V)		AC220V ± 15%	AC220V ± 15%	AC220V ± 15%
Frequency (Hz)		50/60	50/60	50/60
Output Current Range (A) MIG/MMA/TIG		40-180/10-180/10-180	40-200/10-200/10-200	40-250/10-250/10-250
Rated Duty Cycle (%)		10	25	35
Type of Wire Feeder		Built-in	Built-in	Built-in
Wire-feeding Speed (m/min)		2~13	2~13	2~13
Welding-wire Diameter (mm)		0.6-1.0	0.6-1.0	0.6-1.2
Insulation Grade		H	H	H
Housing Protection Grade		IP23	IP23	IP23
Net Weight/Gross Weight (KGS)		12/14	20/22	35/37
Dimension(mm)		580x280x460	700x280x510	760x320x580

### Construction features:

High quality components are used including the German manufactured (INFINEON) IGBT components and the USA (IXYS) diodes. The current sensor is manufactured by USA (HONEYWELL).

- IGBT high frequency inverter DC MIG, MMA, TIG
- Gas/gasless
- Easy operation
- Smooth weld aluminum with spool gun
- Digital display

