



SCREW COMPRESSOR

PERMANENT MAGNET VARIABLE FREQUENCY



 **IE4/IP65** permanent magnet motor.

 **Large size air end, low speed, sufficient air flow.**

 **6PCS heavy-duty bearings, morse taper connection.**

 **Easy to install and maintain. Touch screen control panel.**

*Single phase/3 phase
Both available*



| Model No. | Power (HP) | Discharge pressure (Bar) | Air delivery (L/min) | Tank (L) | Air dryer | Dimension L*W*H(mm) | Air outlet |
|------------|------------|--------------------------|----------------------|----------|-----------|---------------------|------------|
| TSC-4EV | 4 | 8 10 | 175-350 150-300 | x | x | 800*525*755 | 1/2" |
| TSC-4EVT | | | | 100 | x | 1130*525*1040 | |
| TSD-4EFT | | | | 160 | Yes | 1344*525*1040 | |
| TSC-5EV | 5 | 8 10 | 200-400 175-350 | x | x | 800*525*755 | |
| TSC-5EVT | | | | 100 | x | 1130*525*1040 | |
| TSD-5EFT | | | | 160 | Yes | 1344*525*1040 | |
| TSC-7.5EV | 7.5 | 8 10 | 315-630 275-550 | x | x | 800*525*755 | |
| TSC-7.5EVT | | | | 100 | x | 1130*525*1040 | |
| TSD-7.5EFT | | | | 160 | Yes | 1344*525*1040 | |
| TSC-10EV | 10 | 8 10 | 490-980 450-900 | x | x | 1020*590*920 | |
| TSC-10EVT | | | | 160 | x | 1344*590*1200 | |
| TSD-10EFT | | | | 160 | Yes | 1344*590*1200 | |